

## Loughlin Furniture recommend the following product care instructions to extend the life of your Timber Entry Door

- It is ideal for Timber Entry Doors to be maintained every 12 months or as required (kits can be purchased through Loughlin Furniture).
- Due to the nature of solid timber we advise only using a solid timber entry door if there is adequate undercover protection from the elements.
- Excess water (after prolonged rain or storm) on your entry door should be diligently wiped dry to ensure longevity
  of the timber surface.
- No chemical cleaning product(s) should be used directly on timber products.
- A soft damp cloth should be used to clean down the product.

Please contact our team if you have any other questions or concerns about caring for your Loughlin Furniture product.

## Outdoor Polyurethane Finish - How to apply

- 1. Use sand paper provided (or coarser paper if lacquer is very rough) over the entire surface to achieve a smooth even coat.
- 2. Wipe down with a dry microfibre cloth to remove any dirt, dust or debris prior to painting.
- 3. Stir thoroughly before applying.
- 4. Apply with a small roller for the best finishing results (using a paint brush make sure to brush the ship lap or V-groove areas before rolling, ensure to brush excess away before it dries)
- 5. Dry time for coats is approx 8-12 hours at min 20 degrees c. Always check that the finish is completely dry before sanding and re coating. (We recommend waiting 12 hours between coats)
- 8. Clean up tools, containers and spills with water upon completion.

Please note - It is best practise to treat all faces and sides of the product evenly, this ensures the timber will last longer and not want to bow and twist from over sealing on one side more than the other.

The 'Entry Door Care Pack' comes with 500ml of polyurethane finish + sandpaper.



Showroom
Mon—Fri 9am to 3.30pm
Sat 9am to 1pm
Unit 1, 305 Manns Road
West Gosford
Ph 02 4322 2186
info@loughlinfurniture.com.au